

22: Masterflex L/S Peroxide-Cured Silicone Tubing, L/S 15, 25 ft

Cole-Parmer Cat No.EW-96400-15

Features:

- Greater physical compression capability
- Economical, longer tubing life



Specifications:

| Pump Series | L/S |
|---|---|
| Tubing formulation | Silicone (peroxide cured) |
| L/S Masterflex tubing size | 15 |
| Hose Barb Size (in) | 3/16 |
| Tubing ID (mm)/ (in) | 4.8/0.189 |
| Max Flow Rate (mL/min) | 1100 |
| Max Pressure (PSI)/ (bar) | 40 / 2.7 |
| Max Vacuum (mm Hg)/ (" Hg) | 660 / 26 |
| Max Temperature (Dynamic) (° C)/ (° F) | 100 / 212 |
| Min Temperature (Dynamic) (° C)/ (° F) | -40 |
| Max Temperature (° C)/ (° F) | 230 / 446 |
| Min Temperature (° C)/ (° F) | -50 / -58 |
| Suction Lift (ft H₂O)/ (m H₂O) | 29 / 8.8 |
| Length Per Pack (ft)/(m) | 25 / 7.6 |
| Sterilization Method | Autoclave, Ethylene Oxide |
| Description | Peroxide-cured silicone tubing, L/S 15, 25 ft. |
| Origin | U.S.A |